

Notice to Customer:

Please fax the following information to BD Diesel Performance to complete this installation. Fax # 1-604-853-6089

BD Invoice # (if known):					
Customer Information					
Company:			Contact :		
Address:				Zip/Postal Code:	
Phone #			Fax #:		
Email:					
Vehicle Information					
Vin #:					
Mileage at installation:					
Transmission Serial Number :					
		Ins	aller Information		
Company:			Contact:	Contact:	
Name:			Date of Instal	Date of Install:	
Verification of pressures					
Pressure at Idle	(In Drive):			(Should be 60-70 PSI)	
Pressure at wide open throttle (In Drive): (Should be 230-260 PSI with a mechanical gauge)					
** Wide open	throttle press	ures MUST be take	while the transmission	n is in lock up AFTER DRIVE LEARN	
has been completed. (300 PSI Manual Gauge)**					
68RFE Clutch Fluid Index Data Sheet					
Readings Must be done with a 300 PSI Manual Gauge with the					
supplied adapter.					
	INITIAL	AFTER QUICK LEAD	<u></u>	AFTER VALUE'S STABILIZE (50-100 KMS)	
LR	INITIAL	AI TER GOIOR ELA	DITTE LEARN	ATTEN VALUE O OTABILIZE (OO TOO KINO)	
2-4 OR 2C					
UD					
OD					
4C					
Norm N-1 UD					
Alternate 4C					
1 st 2-3 OD					
Alternate 2C					
1 st N-1 UD				(72.122	
	INITIAL	AFTER QUICK LEAD	N DRIVE LEARN	AFTER VALUE'S STABILIZE (50-100 KMS)	
2-4 Shift					
2C					
1st N-UD					
1st 3-4 OD					
LR					
LR					
Alt 2C					
4C					
UD					
UD					
Norm N-D UD					
OD					
OD					
	plicable section	as information differs	ependent on model year.		