


Engine Oil Pan L5P

(114053000)

Installation Guide

Step 1. Vehicle off. Engine cool. Completely drain oil. Overnight, if possible.

Step 2. Remove skid plate, crossmember, then unbolt and support front differential. Lower and secure front differential for easier stock pan removal and installation of larger PPE pan.



Step 3. Remove stock pan bolts.


Step 4. Locate lower, passenger-side bell housing bolt. Remove bolt and save. To make room for the larger pan, the bolt length will be trimmed in later steps.



Step 5. Pry away stock pan from mating surface, using caution for remaining oil.

Remove stock pan.

Step 6. Thoroughly clean mating surface of all old silicone gasket material. Wipe oil off oil pickup.



Step 7. Disconnect transmission coolant lines and secure, up and out of the way, clearing enough room for installation. Tie off lines with a rag.



Step 8. Apply silicone sealant to pan mating surface and around bolt holes.



Step 9. *It is very important not to smear the sealant while installing the new pan. It is recommended you have help in locating the dowel pin, which indexes the pan in the proper position.*

Starting from the rear, angle the pan over the differential as shown. Tip the back of the pan to level, being careful of the sealant. With a spotter's help, lift the pan up into its indexed position, using the dowel as reference.



Once in position, install two bolts on each side (middle) to secure the pan. Finger-tighten bolts to hold pan in position.

Step 10. *Install remaining bolts and torque to 18-22 ft. lbs, starting from the center of the pan and working outward.*

At this time, check drain plug and NPT plug to be sure they're tight.

NOTE: *Allow at least one hour for silicone to set up.*



Step 11. *Check and mark bell housing bolt for trimming. Use a cut-off wheel to trim excess. Reinstall bolt and torque to manufacturer spec.*



Step 12. *Reassemble front differential and torque to manufacturer spec. Reinstall transmission coolant lines, crossmember and skid plate.*

Fill engine with high-quality oil. Check for leaks.

Top off transmission fluid if necessary.

Installation complete.

DISCLAIMER OF LIABILITY

Performance products can increase horsepower above and beyond factory specifications. Additional horsepower creates more stress on the drive-train components, which could result in drive-train failure.

Note regarding emissions-related, non-E.O.-legal products: THESE PRODUCTS ARE LEGAL IN CALIFORNIA ONLY FOR RACING VEHICLES THAT MAY NEVER BE USED, OR REGISTERED OR LICENSED FOR HIGHWAY OR OFF-ROAD USE.

This agreement sets forth the terms and conditions for the use of PPE products. The installation of this product indicates that the Buyer has read and understands this agreement and accepts the terms and conditions. PPE (Pacific Performance Engineering) Inc., its distributors, employees, and dealers (the "Seller") shall not be responsible for the product's proper use and service. The buyer hereby waives all liability claims. The Buyer hereby acknowledges no reliance on the Seller's skill or judgment to select or furnish goods suitable for any particular purpose and that there are no liabilities which extend beyond the description on the face hereof, and the Buyer hereby waives all remedies or liabilities expressed or implied, arising by law or otherwise (including without any obligation of the Seller with respect to fitness, merchantability and consequential damages), or whether or not occasioned by the Seller's negligence. The Seller disclaims any warranty and expressly disclaims any liability for personal injury or damages. The Buyer acknowledges and agrees that the disclaimer of any liability for personal injury is a material term for this agreement and the Buyer agrees to indemnify the Seller and to hold the Seller harmless from any claim related to the item of equipment purchased. Under no circumstances will the Seller be liable for any damages or expenses by reason of use or sale of any such equipment. The Seller assumes no liability regarding the improper installation or misapplication of its products. It is the installer's responsibility to check for proper installation and if in doubt, contact the manufacturer. The Buyer is solely responsible for all warranty issues from the manufacturer.

LIMITATION OF WARRANTY

The Seller gives Limited Warranty as to description, quality, merchantability, and fitness for a particular purpose, productiveness, or any other matter of Seller's product sold herewith. The Seller shall not be responsible for the products proper use and service and the Buyer hereby waives all rights other than those expressly written herein. This warranty shall not be extended, altered or varied except by a written instrument signed by Seller and Buyer.

The Warranty on PPE Manifolds and Up-Pipes Kits, OEM-Length Up-Pipes is three (3) years, a limited lifetime warranty on PPE cast aluminum pans and covers, and a limited lifetime warranty on PPE Transmission Coolers and one (1) year limited warranty on all other PPE products from the date of sale to original buyer and limited solely to the parts contained within the products kit. All products that are in question of Warranty must be returned prepaid to the Seller and must be accompanied by a dated proof of purchase receipt. All Warranty claims are subject to approval by Seller. Under no circumstances will the Seller be liable for any labor charged or travel time incurred in diagnosis for defects, removal, or re-installation - of this product or any other contingent expenses. Under no circumstances will the Seller be liable for any damage or expenses incurred by reason of the use or sale of any such equipment. In the event that the buyer does not agree with this agreement: the buyer may promptly return this product, in a new and unused condition in its original packaging, with a dated proof of purchase to the place of purchase within ten (10) days from date of purchase for a full refund. The installation of this product indicates that the buyer has read and understands this agreement and accepts its terms and conditions.



5011 Brooks St. Montclair CA 91763

PPEdiesel.com

sales@ppediesel.com

Phone: (714) 985-4825