

# Oil System Cleaner

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 12/19/2014

Revision date: 12/19/2014

Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name : Oil System Cleaner  
Product code : OSC-9P

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Oil additive

#### 1.3. Details of the supplier of the safety data sheet

Justice Brothers, Inc.  
2734 Huntington Drive  
Duarte, CA - USA 91010  
T (626) 359-9174 (M-F, 8am-5pm)

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC International +1 (703) 527-3887 24 hr

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Flammable Liquid 4  
Acute Toxicity 3 (Inhalation)  
Skin Irritation 2  
Eye Irritation 2A

#### 2.2. Label elements

##### GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Combustible liquid. Toxic if inhaled. Causes skin irritation. Causes serious eye irritation.

Precautionary statements (GHS-US) :

Keep away from heat/sparks/open flames/hot surfaces.— No smoking. Wear protective gloves/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

#### 2.3. Other hazards

No additional information available.

#### 2.4. Unknown acute toxicity (GHS-US)

4 % of the mixture consists of ingredient(s) of unknown acute toxicity.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable.

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Petroleum Solvent	(CAS No) 64742-47-8	15 - 40	Flam. Liq. 3 Asp. Tox. 1

# Oil System Cleaner

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Name	Product identifier	%	GHS-US classification
Petroleum Solvent	(CAS No) 64742-96-7	15 - 40	Flam. Liq. 3 Skin Irrit. 2 Asp. Tox. 1
2-Pentanol, 4-methyl-	(CAS No) 108-11-2	7 - 13	Flam. Liq. 3 Eye Irrit. 2A STOT SE 3
2-Butoxyethanol	(CAS No) 111-76-2	7 - 13	Flam. Liq. 3 Acute Tox. 4 (Oral) Acute Tox. 4 (Dermal) Acute Tox. 3 (Inhalation) Skin Irrit. 2 Eye Irrit. 2A
Sodium long-chain alkaryl sulfonate	Proprietary	1 - 5	Eye Irrit. 2A

\* The specific chemical identity and exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical advice/attention.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : Toxic if inhaled. May cause respiratory tract irritation. May cause headache, dizziness, nausea, vomiting and malaise.
- Symptoms/injuries after skin contact : Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/injuries after ingestion : May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Treat for surrounding material.
- Unsuitable extinguishing media : None known.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

#### 5.3. Advice for firefighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use special care to avoid static electric charges. Eliminate sources of ignition.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

##### 6.1.2. For emergency responders

No additional information available.

#### 6.2. Methods and material for containment and cleaning up

- For containment : Eliminate sources of ignition. Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

# Oil System Cleaner

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

### 6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharge. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only non-sparking tools.

Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Keep cool.

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Petroleum Solvent (64742-47-8)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.
Petroleum Solvent (64742-96-7)		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.
2-Pentanol, 4-methyl- (108-11-2)		
USA ACGIH	ACGIH TWA (ppm)	25 ppm
USA ACGIH	ACGIH STEL (ppm)	40 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	25 ppm
2-Butoxyethanol (111-76-2)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	240 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
Sodium long-chain alkaryl sulfonate		
USA ACGIH	ACGIH TWA	Not applicable.
USA OSHA	OSHA PEL (TWA)	Not applicable.

### 8.2. Exposure controls

Appropriate engineering controls : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Hand protection : Wear chemically resistant protective gloves.

Eye protection : Wear eye protection.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Environmental exposure controls : Maintain levels below Community environmental protection thresholds.

Other information : Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

# Oil System Cleaner

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid.
Appearance	: Clear.
Colour	: Light amber.
Odour	: Hydrocarbon.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: > 178.3 °C (> 353 °F)
Flash point	: 80 °C (176 °F)
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: No data available.
Relative density	: 0.82 g/cm <sup>3</sup>
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: 647.26 mm <sup>2</sup> /s
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

#### 9.2. Other information

No additional information available.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No dangerous reaction known under conditions of normal use.

#### 10.2. Chemical stability

Stable under normal storage conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

#### 10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition.

#### 10.5. Incompatible materials

Strong oxidizing agents.

#### 10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Toxic if inhaled.

Oil System Cleaner	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 2.0 but ≤ 10.0 mg/l/4h

# Oil System Cleaner

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

<b>Petroleum Solvent (64742-47-8)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.2 mg/l/4h

<b>Petroleum Solvent (64742-96-7)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat	> 5.28 mg/l/4h

<b>2-Pentanol, 4-methyl- (108-11-2)</b>	
LD50 oral rat	2590 mg/kg
LD50 dermal rabbit	2880 mg/kg

<b>2-Butoxyethanol (111-76-2)</b>	
LD50 oral rat	470 mg/kg
LC50 inhalation rat	450 ppm/4h

<b>Sodium long-chain alkaryl sulfonate (Proprietary)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met.
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Based on available data, the classification criteria are not met.

<b>2-Butoxyethanol (111-76-2)</b>	
IARC group	3 - Not classifiable
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity

Reproductive toxicity	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met.
Specific target organ toxicity (repeated exposure)	: Based on available data, the classification criteria are not met.
Aspiration hazard	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Toxic if inhaled. May cause respiratory tract irritation. May cause headache, dizziness, nausea, vomiting and malaise.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/injuries after ingestion	: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: May cause long-term adverse effects in the aquatic environment.
-------------------	---

### 12.2. Persistence and degradability

<b>Oil System Cleaner</b>	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

<b>Oil System Cleaner</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

No additional information available.

### 12.5. Other adverse effects

Effect on ozone layer	: No additional information available.
-----------------------	--

# Oil System Cleaner

## Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Effect on the global warming : No known ecological damage caused by this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Additional information : Handle empty containers with care because residual vapours are flammable.

### SECTION 14: Transport information

In accordance with DOT

#### 14.1. UN number

UN-No.(DOT) : NA1993

#### 14.2. UN proper shipping name

DOT Proper Shipping Name : Combustible liquid, n.o.s. (Petroleum; 2-Pentanol, 4-methyl-; 2-Butoxyethanol)

Department of Transportation (DOT) Hazard Classes : Combustible liquid

Packing group (DOT) : III

#### 14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

#### 15.2. US State regulations

##### Oil System Cleaner

State or local regulations	This product contains a chemical known to the State of California to cause cancer.
----------------------------	--

### SECTION 16: Other information

Indication of changes : None.


Date of issue : 12/19/2014

Other information : None.

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



*Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.*